

UVA-M

Circular fire damper with actuator

Certified fire dampers signed with CE mark.

On demand can be made of stainless steel (AISI 304 or AISI 316L).

Actuators 24V or 230V.

Additionally: actuator equipped with Thermal tripping device or actuator equipped with Thermal tripping device and connection plugs.



| Diameter D | Length | Insertable part length L ₁ | Weight, kg | Actuator (24V) | Actuator (230V) |
|------------|--------|---------------------------------------|------------|----------------|-----------------|
| | | | | Code | |
| 100 | 386 | 40 | 2,7 | 751800069 | 751800091 |
| 125 | 386 | 40 | 3,1 | 751800070 | 751800092 |
| 160 | 386 | 40 | 3,7 | 751800071 | 751800093 |
| 200 | 386 | 40 | 4,4 | 751800072 | 751800094 |
| 250 | 386 | 40 | 5,4 | 751800073 | 751800095 |
| 315 | 386 | 40 | 6,7 | 751800074 | 751800096 |
| 355 | 505 | 65 | 8,8 | 751800029 | 751800123 |
| 400 | 505 | 65 | 10,1 | 751800030 | 751800124 |
| 450 | 505 | 65 | 11,7 | 1023384 | 751800125 |
| 500 | 505 | 65 | 13,4 | 751800028 | 751800126 |
| 560 | 505 | 65 | 15,5 | 751800117 | 751800127 |