

(EU) No 1254/2014 data

Trade mark	Komfovent
Model	DOMEKT-CF-700-H-L1-F7/M5-C6M-X
SEC (climate zone 1 / 2 / 3)*	-82,7 / -43,2 / -17,9 kWh/(m ² ·a)
SEC class	A+
Typology	Bidirectional
Drive type	Variable speed drive
Heat recovery system	Recuperative
Thermal efficiency	90 %
Maximum flow rate	621 m ³ /h
Fan drive electric power	180 W
Casing sound power level	46 dBA
Reference flow rate	0,121 m ³ /s
Reference pressure difference	50 Pa
SPI	0,25 W/(m ³ /h)
Control factor	0,65
Control typology	Local demand control (ahu flow rates controlled by more than one sensor)
Maximum external leakage	1,5 %
Maximum internal leakage	1,5 %
Filter warning	When filter gets dirty, the unit control panel notifies the user about the need to change it. Dirty filters cause increased energy consumption, which decreases performance and energy efficiency of the unit, so it is very important to change the filters regularly.
Instructions	www.komfovent.com
AEC (climate zone 1 / 2 / 3)*	714,3 / 177,3 / 132,3 kWh/annum
AHS (climate zone 1 / 2 / 3)*	9181,5 / 4693,4 / 2122,3 kWh/annum
*Climate zones 1 / 2 / 3	1 - cold / 2 - average / 3 - warm

ENERG Y IJA
енергия · ενέργεια IE IA

DOMEKT-CF-700-H-L1-F7/M5-C6M-

Komfovent X

A+

46
dB

621 m³/h

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016 1254/2014

Note:

Measurements executed according to the EN 13141-7:2015 standard.